

## SewperCoat<sup>®</sup> Packaging and Coverage Information

	SewperCoat <sup>®</sup> 2000HS	SewperCoat <sup>®</sup> P.G.
Bag (lb)	50	65
Truckload Quantity (bags)	896	686
Bags/Pallet	64	49
Pallet/Truck	14	14
Weight/Pallet (tons)	1.60	1.62
Weight/Truck (tons)	22.40	22.65
Wet Density: Weight/Ft <sup>3</sup>	148-155 lb/ft <sup>3</sup>	148-155 lb/ft <sup>3</sup>
Material/ft <sup>2</sup> at ½" application thickness (includes rebound)	8.0 lb.	5.6 lb.
Material/ft <sup>2</sup> at 1" application thickness (includes rebound)	15.5 lb.	11.0 lb.
Minimum Installation Thickness	1/2"	1/2"
Working Time	1 hour	2 hours
Method of Application	dry-gunite	low-pressure, wet spray

SewperCoat<sup>®</sup> is a ready-to-use mortar designed specifically for the municipal wastewater industry to provide a structural, abrasion and corrosion-resistant, protective lining against biogenic corrosion relative to hydrogen sulfide (H<sub>2</sub>S) found in wastewater environments.

For more information, please contact the SewperCoat<sup>®</sup> Market Manager at  
1-800-524-8463.

Email inquiries can be sent to: [kus.info@kerneos.com](mailto:kus.info@kerneos.com).

The Kerneos Inc. web page is located at:  
<http://www.KerneosInc.com>

*KERNEOS ASSISTANCE IN TECHNICAL PLANNING, SPECIFICATIONS, AND/OR INSTALLATION RELATING TO ITS PRODUCT IS PURELY ADVISORY AND IS NOT A SUBSTITUTE FOR PROFESSIONAL ENGINEERING JUDGMENT. ANY SUCH ASSISTANCE (INCLUDING WITHOUT LIMITATION THIS DOCUMENT) AND ANY WRITTEN OR ORAL COMMUNICATION MADE IN CONNECTION HEREWITH, DOES NOT WARRANT THE SUCCESS OF ANY APPLICATION OR ANY OTHER MATTER, AND DOES NOT EXTEND A WARRANTY, EXPRESS OR IMPLIED, NOT SET FORTH IN THE KERNEOS WRITTEN WARRANTY STATEMENT. A COPY OF THE KERNEOS WRITTEN WARRANTY STATEMENT IS AVAILABLE UPON REQUEST.*